

EH130 Stat

ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

| PRODUCT SPECS | |
|---|------------------------|
| Capacity <i>lbs</i> | 130 |
| Cylinder Diameter <i>inch</i> | 42.5 |
| Cylinder Depth <i>inch</i> | 24.4 |
| Cylinder Volume <i>cu ft</i> | 20.1 |
| Net Weight <i>lbs</i> | 4260 |
| Crated Weight <i>lbs</i> | 4636 |
| Machine Dimensions <i>inch</i> WxDxH | 61.8 x 58.8 x 75.8 |
| Door Opening <i>inch</i> | 22 |
| Floor to Door <i>inch</i> | 32 |
| Shipping Dimensions <i>inch</i> WxDxH | 66.5 x 64.8 x 85 |
| Washing Speed <i>rpm</i> | 13/18/24/30/36 |
| Spin Speeds <i>rpm</i> | 72/300/450/625/800 |
| G-force | 3.13/54/122/236/387 |
| Static Force Transmitted <i>lbs</i> | 4888 |
| Dynamic Force Transmitted <i>lbs</i> | 692 |
| Frequency of Dynamic Force <i>Hz</i> | 13.3 |
| Available Voltages/Wire Conductor/Amp | |
| Hot Water (standard) | 208-240/60/3, 3W+G, 25 |
| Hot Water (standard) | 440-480/60/3, 3W+G, 16 |
| Electric Auxiliary Heat (optional) | 208/60/3, 3W+G, 100 |
| Electric Auxiliary Heat (optional) | 240/60/3, 3W+G, 125 |
| Steam Auxiliary Heat (optional) | 208-240/60/3, 3W+G, 25 |
| Steam Auxiliary Heat (optional) | 440-480/60/3, 3W+G, 16 |
| Drain Diameter <i>inch</i> | 3 |
| Water Inlets <i>inch</i> | 2 @ 1 |
| Recommended Water Pressure <i>PSI</i> | 30-60 |
| Water Flow <i>gal/min</i> | 26 |
| Steam Connection <i>inch</i> | 3/4 |
| Steam Pressure (optional) <i>PSI</i> | 29-87 |
| Steam Flow (optional) <i>lbs/h</i> | 397 |
| Total Power <i>kW</i> | 7.3 |
| Electrical Heating Power (optional) <i>kW</i> | |
| 208/60/3 | 27.9 |
| 240/60/3 | 35.8 |

* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

